

Inventor's name : **Henri Duong**  
Nationality : **French**  
Residence : **4627 Louise Avenue, Whitehall, Ohio-43213**  
**the United States of America**

**Title of the Invention**

- **Automatic Braking Systems equipped in Automobiles, Cars, Trucks, Motorcycles, Trains and All Vehicles..**

**Cross-Reference to Related Applications**

- **"Not Applicable"**

**Statement Regarding Federally Sponsored Research or Development**

- **"Not Applicable"**

**Reference to a Microfiche Appendix**

- **"Not Applicable"**

**Background of the Invention**

- **It came from my imagination in the field of invention since traffic accident often happens where it costs human lives daily even if people find unsafely crossing the streets. My imagination turns to develop step by step certain technical components related to my invention and I finally discover the structures of my invention by braking a car automatically through modern technical operation.**

**Brief Summary of the Invention**

- **Automatic braking system owns its original fundamentals and structures. Automatic braking systems are to be equipped in automobiles, cars, trucks, motorcycles, trains and all vehicles.. The advantages of the invention are to prevent killing, hurting human beings and damaging materials from traffic accidents.**

- **The system composes of essential parts : Infrared lenses/sensors, radars or equivalent equipment, motor, triangle wheel with inner triangle wheel or hexagon/multiple-angle wheel, extension at upper part of pedal, electric wires, pin, contacts for driver**

use, sonorous signal lamp, round wheel, iron bars, bracket arms, springs, rewind springs, strong springs, adjustable switches, iron lock switches, double spinning motor, toothed spindle, nut with frame, short tube, axis with groove part, gear, frame, outlet kit, connecting rod kit, roller & ball bearings, rubber cover wheel in a double pulley, moving frame, hoses, extension of braking rod, cover, nut, clip, rectangular bracket, a lock, oscillator, arm, safety covering box, alarm, frame with moving ball, mini-motor with half wheel ..

#### Brief Description of the Several Views of the Drawing

- "Not Applicable"

#### Detailed Description of the Invention

- Description creates various structures of the unique Automatic braking system of its original fundamentals for purpose of fitting different types and structures of automobiles in automobile industry.

- Infrared lenses/sensor or radar which has anti-frozen or heating system against snow is equipped in front of a car to view object or person who crosses a street accidentally at certain distance while a car is running, the sensor(s) sends information by electric wire.. to switch the braking motor on immediately to brake the car by itself automatically.

- The motor runs by car electric power, its axis is equipped with a triangle wheel. Whenever the triangle wheel turns to its edge point pressing at the opposite side of upper pedal, it is the moment it brakes the car as if a driver brakes his pedal at the lower part. Brake will be released while flat part of this wheel touches the upper pedal as a driver releases his foot off the pedal. There is a ball bearing with pin fixed firmly at the surface of wheel nearby its flat part corner where a spring is fastened from pin to a moving ball of motor frame pulling the wheel at the right position after each spin so as to unlock the brake. Extension at upper part of a normal pedal is needed for a triangle wheel to brake on it at the opposite side. Further, we set three iron switches inside the motor to lock edge points of an inner triangle wheel at braking position and it will be released by driver's contact then we fix the motor between two strong springs or a single spring at its bottom to support its spin.

- However it depends on structures of vehicles, the simple way is to equip a braking motor with the same equipment at upper part of a pedal at driver's side, its wheel will brake directly on it without requirement of pedal extension.

We can use a round wheel to brake as well, motor axis is particularly fixed at the border between center and rim of the wheel in this way. A sensor has ability to command the motor rotating at both sides : It turns right to brake the car automatically once object is detected, it turns left to release the pedal whenever object/person disappears in front of the sensor or from left to right.

The motor holds an iron bar out close to its wheel on which is made with a bracket arm. Whenever wheel revolves to its braking summit, its bracket will be blockaded by the bar where there is an iron switch to switch motor off & to lock wheel at braking position and it will be released by driver's contact to left rotating at release position where adjustable bracket locks its wheel to motor switch bar, it is good to use pedal movement with a function switch instead, we may choose a simple motor with outer or inner rewind spring at back spin.

- It makes sense using screw & unscrew rotating by a double spinning motor which is installed in a frame with a nut as its outlet, since toothed spindle of the motor engages with & through this gear-nut, it turns right out braking on the pedal part, there are two iron switches set in the frame to switch motor off & to lock it at its end part during braking and it will be released by driver's contact to left spin in releasing at a position with same lock devices at the other end. If we equip a simple motor instead at its left spin, spindle will slot into a spring before inserting to gear-nut. A sensor functions as usual.

- Similarly, we install a frame with a short tube outlet where motor axis engages in it, this axis has its groove end part connected with a gear of a double revolving motor, spin is its braking action against the pedal part. If we replace with a simple motor, an axis needs to be fastened by outer or inner rewind spring to its gear or we link a spring at the end of an axis to the frame, its function includes a sensor with pedal switches to command a mini-motor with half wheel at outer frame to lock and unlock axis at braking position and same at releasing position with driver's contact.

- Another suggestion is to build an additional outlet device from original booster/master cylinder besides the brake-by-pedal one, this extra outlet possesses spring force to push its rod out before braking, this rod is linked with a connecting rod kit with roller & ball bearings fixed at the border between center and rim of a round wheel, this wheel engages a right & left spinning motor with adjustable at distance, an infrared lenses/sensor directs its braking spin with necessary switch, lock device.

- Discovery shows the above complete connecting rod bearing kit & extra outlet can place on a moving frame where we fix a ball bearing in the center of wheel,

this wheel will automatically connect (to brake) and disconnect (to release) to a rubber cover wheel manufactured as a part of double pulley turning by car engine to replace a motor, the frame moves with oscillator or with spring to oscillate commanded by a sensor, driver's contact, lock & switch device.. Certain part of fluid pipe needs changing to hose for moving adaptation.

- It sounds economical if we lengthen horizontally car original braking rod to certain length and bend it down where we insert a cover with a small spring before passing it through a hole behind car frame ending with a nut and clip. At driver's side, we simply lock two springs from a hidden frame to both ends of an iron bar then we place a rectangular bracket among them to drive the bar whose outer part is against bending part of the rod, the motor drives its bracket to brake and spring force releases. There are switch & lock switch device placing somewhere at one side of the bar to turn motor off by spin under function of an infrared lenses/sensor, driver's contact.. A stronger rewind spring is adapted for brake pedal if necessary and smaller spring is for braking rod.

- On the contrary, the simplest method is to use a lock with piston against the above horizontal bending part of braking rod or car pedal part, we use oscillator, rewind springs or equivalent device switching it to both sides; to brake & to release piloted by a sensor and necessary device.

- Security recommendation : All braking devices must be covered safely against possible accident during automatic braking operations. Or the entire inventive braking systems can be modified and equipped at the opposite side of pedal parts as well by pulling to brake instead of pushing action to the same effect.

- Increase ordinary energy of a sensor/radar can detect at longer distance, an appropriate motor will brake its car fast enough to stop its running. Driver may switch off the whole system by a special contact when necessary. Sonorous signal lamp rings while Automatic Braking System is turned off, it is to make sure the system is on when a car starts.

- Automatic braking system is a new invention to be equipped in automobiles, cars, trucks, motorcycles, trains and all vehicles.. that do not possess such a system.

- Further proposal is to have small infrared lenses/sensor equipments equipped at both right & left sides of a car with ability to sound the alarm once running cars extremely approach each other.